

IMPROVED

# SPITA ResQ-tape®


Self-fusing silicone tape






EU

## PROFESSIONAL

- Insulates **12** Kilovolts (per layer)
- Heat resistant up to 260° Celsius
- Remains flexible till -90° Celsius
- Never gets gummy or sticky
- Self-fusing
- Pressure resistant up to **12 Bar** (with diameter of 25mm)



- Remains flexible
- Can be applied under water
- UV-resistant
- Stretchable up to **400%**
- Waterproof - Airtight
- Permanent seal
- Resists fuels, oil, acids, solvents and salt




## FAST AND EASY TO USE:

1 


Begin by peeling liner away from SPITA ResQ-tape.

2 

Press SPITA ResQ-tape firmly on object being wrapped, hold in place and begin first wrap completely over itself.

3 

While holding SPITA ResQ-tape in place, begin **STRETCHING** at 3 to 4 times its length and wrap object with 50% overlap to ensure a proper seal.

4 

To complete wrapping of object, wrap SPITA ResQ-tape completely over previous layer and press firmly.



# SPITA ResQ-tape<sup>®</sup>

Self-fusing silicone tape



EU12TI

## PROFESSIONAL

**SPITA ResQ-tape**, made of pure silicone, is the most versatile self-fusing repair tape for emergencies and all-purpose repairs. **SPITA ResQ-tape** is the strongest, fastest-fusing repair tape and can be used under very critical conditions. Just by stretching and wrapping it around an object onto itself, it will quickly and easily create a permanent airtight, waterproof seal in just seconds! It can even (without cleaning first) be used on dirty and wet surfaces. It will remain flexible and not become brittle after being exposed to sunlight.

## UNIVERSAL REPAIR TAPE

**SPITA ResQ-tape** let you repair leaks on plumbing and hoses in a flash, make underwater repairs, use it on electrical wiring or as shrink-wrap, wrap tool handles, connect two separate objects and much...much more!

**SPITA ResQ-tape** is easy to remove and will never leave a residue!!

### IMPORTANT WITH PRESSURE LEAKS

Only when tape is stretched to the max, it will be able to withstand the pressure!

① Apply first wrap with 100% overlap before the leak.

**Stretch to the max<sup>®</sup>**

② Continue wrapping with 50% overlap.

③ Finish with last wrap 100% overlapping previous layer.



**US Military Spec**  
CID A-A-59163  
Type I & II (formerly MIL-I-46852C)



**UL Listed**  
SPITA ResQ-tape is UL (Underwriter Laboratories) Listed



### IMPORTANT WITH ELECTRICAL WORK

① Apply first wrap with 100% overlap before area of insulation



② Continue wrapping with 50% overlap.

③ Finish with last wrap 100% overlapping previous layer and press all wraps firmly.

**SPITA ResQ-tape doesn't need to be stretched in order to fuse. However a little stretching will increase the speed of the fusing process!**



**SPITA ResQ-tape has infinite uses! Here are a few suggestions:**

- ✓ Emergency repairs on all vehicles, machines and boats
- ✓ Seal leaky hoses, pipes, tubing & fittings
- ✓ Wrap tools and handles for a perfect non-slip grip
- ✓ Whipping rope ends

- ✓ Electrical insulation of wires and connectors
- ✓ Waterproof electrical connectors and terminals
- ✓ Use it as an emergency fan belt or O-ring
- ✓ Marking lines and chains

- ✓ Corrosion protection
- ✓ Works even over wet, dirty and oily surfaces
- ✓ Works under water
- ✓ Keep it on board for emergencies

Dimensions:  
(width x length x thickness)  
25,4 mm x 3,6 mtr x 0,5 mm  
50,8 mm x 3,6 mtr x 0,5 mm

Shelf life > 10 years when tape is stored in the dark at normal temperature!

Lifespan after application > 25 years.

Attention:  
Red guideline on tape guarantees that tape is **12 bar** pressure resistant and insulates **12kV** per layer.

Available in the following colours:

BLACK    RED    WHITE    BLUE    ORANGE    YELLOW    GREEN    CLEAR    GREY



Please visit our website for further information:  
[www.tapeinnovation.de](http://www.tapeinnovation.de)  
[www.resqtape.eu](http://www.resqtape.eu)



**Tape Innovation GmbH**  
Dahlemstrasse 37, 53359 Rheinbach  
Tel.: +49 (0)2225 999 6680, Fax: +49 (0)2225 999 6685  
Email: [info@tapeinnovation.de](mailto:info@tapeinnovation.de)

Attention: This product is provided without warranty, either expressed or implied, of fitness for a specific purpose. Because conditions and methods of use are beyond the manufacturer's control, neither manufacturer nor seller will assume any responsibility for the use or misuse of this product. This includes, but is not limited to, any consequential damages. **SPITA ResQ-tape** is a trademark of G&G Trading International B.V., Harderwijk (NL).

Powered by